



GENERAL NOTES

1. RIGHT-OF-WAY WIDTHS AND EASEMENTS SHOWN ARE MINIMUM REQUIREMENTS FOR NEW STREETS. MEASUREMENTS MAY NEED TO BE ADJUSTED TO MATCH EXISTING FACILITIES.
2. PAVED WIDTH IS MEASURED FROM EDGE OF TRAVELWAY (GUTTER).
3. STREET SECTION MAY BE INCREASED BASED ON GEOTECHNICAL EVALUATION AND PAVEMENT DESIGN.
6. SUBGRADE AND CSTC, INCLUDING GRAVEL SHOULDER SHALL BE COMPACTED TO 95%. COMPACTION AND TESTING REQUIREMENTS PER CHAPTER 9 OF SPOKANE VALLEY STREET STANDARDS.
7. SIDEWALK WIDTH SHALL BE PER STREET CLASSIFICATION, ZONING AND STANDARD PLAN R-103.
8. STREET SECTION AND CLASS OF MATERIALS SHALL BE PER CHAPTER 8, PAVEMENT DESIGN.



APPROVED BY:

A blue ink signature of Robert B. Blegen.

ROBERT B. BLEGEN, P.E.
PUBLIC WORKS DIRECTOR

TYPICAL STREET
SECTION HALF STREET

STANDARD PLAN NO.
R-119

PUBLICATION DATE: 03/2025

REVISION NO.: 01